

Pull-Type Manure Spreader



Horizontal Distributor



Vertical Distributor



Berma Distributor



TR30T & TR32T



TR34T

| MODEL SPECIFICATIONS | | | |
|------------------------------------|--------------------|----------|----------|
| MODEL | TR16T | TR20T | TR22T |
| DIMENSIONS (INCHES) | | | |
| A - OVERALL LENGTH | 354 | 354 | 378 |
| B - INSIDE BOX LENGTH | 240 | | 264 |
| C - INSIDE BOX DEPTH | 39 | | |
| D - INSIDE BOX WIDTH | 72 | 84 | |
| E - OVERALL HEIGHT | | | |
| - TIRE OPTION USED | 385R/22.5 | 1600R/20 | 1600R/20 |
| - TOP OF BEATERS | 98 | 102 | 102 |
| F - LOADING HEIGHT | 81 1/2 | 86 1/2 | 86 1/2 |
| G - OVERALL TREAD WIDTH | 117 | 128 | 128 |
| SPECIFICATIONS | | | |
| MAXIMUM NET LOAD - POUNDS CAPACITY | 32,000 | 40,000 | 44,000 |
| CUBIC FEET - STRUCK LEVEL | 396 | 460 | 508 |
| DISTRIBUTORS | | | |
| NUMBER STRANDARD | 20 | 24 | 24 |
| REPLACEABLE TEETH DIAMETER | YES | | |
| LOWER DISTRIBUTOR | 30 | 30 | 30 |
| UPPER DISTRIBUTOR | 26 | 26 | 26 |
| SPEED - ALL BEATERS -RPM | | | |
| LOWER DISTRIBUTOR | 300 | 300 | 300 |
| UPPER DISTRIBUTOR | 225 | 225 | 225 |
| REMOVEABLE DISTRIBUTOR ASSEMBLY | YES | | |
| APRON | | | |
| NUMBER | 2 | | |
| SHAFT DIAMETER | 2" DRIVE & IDLER | | |
| SPROCKETS | 8 TOOTH | | |
| CHAIN | PINTLE D667K | | |
| SLAT SIZE | 1/4" X 1 1/2" X 2" | | |
| DRIVE | HYDRAULIC | | |
| FRONT PANEL AND SIDES | PE POLYMER | | |
| FLOOR | PE POLYMER | | |

- Twisted Concave Shovels
- Easy Removal of Distributor
- Easy Controls
- Reversible Clevis Hitch
- Chisel Point Teeth to Grab Material

Available in 16, 20, 22, 30, 32 or 34 Ton Models.

