

SPREAD-ALL 

Truck Model



MODEL SPECIFICATIONS		
MODEL	TK20T	TK22T
DIMENSIONS (INCHES)		
A - OVERALL LENGTH	N/A	N/A
B - INSIDE BOX LENGTH	240	264
C - INSIDE BOX DEPTH	39	
D - INSIDE BOX WIDTH	84	
E - OVERALL HEIGHT		
- TIRE OPTION USED	N/A	N/A
- TOP OF BEATERS	122	122
F - LOADING HEIGHT	96	96
G - OVERALL TREAD WIDTH	N/A	N/A
SPECIFICATIONS		
MAXIMUM NET LOAD - POUNDS CAPCITY	40,000	44,000
CUBIC FEET - STRUCK LEVEL	460	508
DISTRIBUTORS	2	
NUMBER STRANDARD	24	24
REPLACEABLE TEETH	YES	
DIAMETER		
LOWER DISTRIBUTOR	30	30
UPPER DISTRIBUTOR	26	26
SPEED - ALL BEATERS -RPM		
LOWER DISTRIBUTOR	300	300
UPPER DISTRIBUTOR	225	225
REMOVEABLE DISTRIBUTOR ASSEMBLY	YES	
APRON		
NUMBER	2	
SHAFT DIAMETER	2" DRIVE & IDLER	
SPROCKETS	8 TOOTH	
CHAIN	PINTLE D667K	
SLAT SIZE	1/4" X 1 1/2" X 2"	
DRIVE	HYDRAULIC	
FRONT PANEL AND SIDES	PE POLYMER	
FLOOR	PE POLYMER	



Vertical Distributor



Berma Distributor

**20, 22, 26, &
34 Ton or
Bigger
Models
Available.**



Horizontal Distributor

**West Point
Implement
& Design**

2074 Hwy 275 West Point, NE 68788
www.westpointimp.com (402) 372-2408
Here for you yesterday, today + tomorrow!

